



CDT Underground, LLC.

902 North Junett
Tacoma, WA. 98406
253 677-3478

COPPER BONDED GROUND RODS

CDT Underground, LLC., supplies ERITECH copper bonded ground rods which provides the physical connection to the earth and is the instrument to dissipate current into it. ERITECH copper bonded ground rods are corrosion resistant with a minimum tensile strength of 80,000 psi and exceed the requirements of ANSI/UL 467, CSA, ANSI/NEMA GR-1.

Ground rods are available in sizes 3/8" to 1" in lengths from 5' to 15' and are packaged in bundles.

Markets served by CDT include CATV, telecommunications, utility and DOT.

COPPER BONDED GROUND RODS

PART#	DIAMETER (in.)	LENGTH (ft.)	PACKAGE QTY	WEIGHT PER 100
613880	3/8	8	5	270
611380	1/2	8	5	553
611300	1/2	10	5	738
615850	5/8	5	5	420
615860	5/8	6	5	509
615880	5/8	8	5	680
615800	5/8	10	5	844
615812	5/8	12	5	1000
615815	5/8	15	5	1275
613460	3/4	6	5	750
613480	3/4	8	5	1000
613400	3/4	10	5	1240
613412	3/4	12	5	1480
613415	3/4	15	5	1850
614400	1	10	5	2204

