



CDT Underground, LLC.

902 North Junett
Tacoma, WA. 98406
253 677-3478

HDPE TONEABLE CONDUIT

CDT Underground, LLC., provides HDPE Toneable conduit which is used to locate underground conduits. This specialized conduit is intended for use in underground installation into main conduit, open trench and directional bore applications.

HDPE Toneable conduit is manufactured in compliance with ASTM F2160, D3350 and NEMA TC7. It has an 18 awg. solid copper wire extruded unto the outside wall of the conduit which allows for ease of extraction of the copper conductor when in need of splicing or terminating. Toneable conduit is available in sizes 1-1/4" to 4" in continuous lengths on reels or coils in numerous colors and stripe combinations for ease of identification.

Options available include pre-lubricated inside walls, pre-installed pull tapes and ropes, pre-installed cable-in-conduit and sequential foot or meter markings.

Markets served by CDT include CATV, telecommunications, utility and DOT.

STONEABLE CONDUIT SPECIFICATIONS

DUCT SIZE	SCH 40		SDR 13.5		SDR 11		
	NOM OD	MIN WALL	NOM ID	MIN WALL	NOM ID	MIN WALL	NOM ID
1-1/4"	1.660	0.140	1.360	0.123	1.394	0.151	1.338
1-1/2"	1.900	0.145	1.590	0.141	1.599	0.173	1.534
2"	2.375	0.154	2.047	0.176	2.002	0.216	1.917
3"	3.500	0.216	3.042	0.259	2.950	0.318	2.825
4"	4.500	0.282	3.896	0.333	3.794	0.409	3.633

