902 North Junett Tacoma, WA. 98406 253 677-3478

PVC SPLIT DUCT

CDT Underground, LLC., supplies Conduit Repair Systems' Split Duct which is an innovative and efficient product that is great for enclosing fiber optics, cables, and repairing damaged conduit. When snapped together, the unique interlocking design of Split Duct creates a smooth tight seal protecting the cable or fiber optics from weathering. No tape, plastic, or metallic straps are needed to seal or provide extra strength to the Split Duct.

PVC Split Duct is available in sizes 1" to 6" in a SCH40 wall, 2" in a SCH80 wall and 4" in a Type C Conduit. It is supplied in 10' lengths, plain end, gray in color.

Markets served by CDT include CATV, telecommunications, utility and DOT.

SCHEDULE 40 SPLIT DUCT SPECIFICATIONS

DUCT SIZE	NOMINAL OD	NOMINAL ID	MIN ORDER QTY	WEIGHT PER FOOT (lbs)
1"	1.315	1.049	10 FEET	0.450
1-1/4"	1.660	1.38	10 FEET	0.550
1-1/2"	1.900	1.61	10 FEET	0.650
2"	2.375	2.067	10 FEET	0.850
2-1/2"	2.875	2.469	10 FEET	1.050
3"	3.500	3.068	10 FEET	1.300
4"	4.500	4.026	10 FEET	1.850
5"	5.563	5.047	10 FEET	2.450
6"	6.625	6.065	10 FEET	3.400

SCHEDULE 80 PVC SPLIT DUCT SPECIFICATIONS

	DUCT SIZE	NOMINAL OD	NOMINAL ID	MIN ORDER QTY	WEIGHT PER FOOT (lbs)
Ī	2"	2.375	1.939	10 FEET	1.200

TYPE C PVC SPLIT DUCT SPECIFICATIONS

	DUCT SIZE	NOMINAL OD	NOMINAL ID	MIN ORDER QTY	WEIGHT PER FOOT (lbs)
ſ	4"	4.350	4.060	10 FEET	1.150

